

Ideal for maintenance work, the EASYCUT K35F is benefits from Inverter technology.

Internal air compressor

With its internal compressor, the plasma does not require an external supply of compressed air.

Quality cutting without distortion

The plasma allows high quality cutting even on painting surfaces:

- Up to 15 mm steel, stainless steel and cast iron.
- Up to 10 mm aluminium and copper.

No HF Start

With the « Pilot Arc » system, the arc starts without having any contact with the welding sheet. Starting without HF avoids any electromagnetic interference (radio, computers, phones, medical equipment, etc...).

Easy to use, fast and safe

- Torch: 4m with safety trigger to avoid accidental start.
- Internal compressor (noise): 60/70 Db.

P400 Reinforced protection for the use with generators and against permanent overvoltage up to 400V (factory tested).

PFC PFC feature: Power factor correction: regulates and uses the power supply more efficiently.

AD It is equipped with an anti-dust fan system which protects the electronics from dust.



Supplied with :



2 m
10 mm²



MT 35 K
4 m

ref. 031036

✓

✓


PERFORMANCE

Capacity	Thickness
Separation	15 mm
Clean cut	10 mm

Accessories and consumables



Consumables box
039964



Compass kit
040205



PLASMA 600 trolley
040298

50/60hz	16A	min▷max	Max cut		Clean cut		Air system		EN60974-1 (40°C)		cm/kg	Protected & compatible POWER GENERATOR (+/- 15%)	
			Acier Steel	Alu	Acier Steel	Alu	Pressure bar	L / min	Kompressor inside	IA (100%)			X% (12 max)
230V	16A	10▷35A	15	10	10	8	included	✓	20A	26A 60%	28x52x46 / 30	8 kW	10 kVA